CUSHMAN

MODEL: HAULER 1500X
TYPE: GASOLINE POWERED TRUCK
MODEL YEAR: 2014
Part No:. 630111

PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

Engine: 16 hp (11.9 kW) rated, 4 cycle, 29.2 ci (480 cc) V-Twin, air-cooled Vanguard

- **Valve Train:** Overhead valve
- **Lubrication:** Pressurized oil system, spin-on oil filter
- **Balancer:** Internal counter rotating balance shaft
- **Fuel System:** Fixed float bowl with remote pulse fuel pump
- **Ignition:** Electronic spark/magneto
- **Air Cleaner:** Replaceable dry cartridge w/permanent pre-filter/remote air

Electrical: Starter/Generator, solid-state regulator, 12 Volt maintenance free battery (525 CCA, 60 minute reserve)
Drive Train: Automatic, continuously variable transmission (CVT). Locking rear axle (Operator selectable from center console)
Brakes: Dual rear wheel hydraulic self-adjusting drum brakes. Hand operated park brake located in center console
Transaxle: Differential with helical gears, ground speed governor, forward/reverse
Seating: Two bucket seats
Cargo Bed: Roto-molded cross-linked polyethelene. Lifts for access to powertrain. Removable hinged multi-position tailgate requires no latch mechanism

PRODUCT OVERVIEW

Dimensions	
Overall Length	113.5 in (288 cm)
Overall Width	48.5 in (123 cm)
Overall Height (No Canopy)	52.5 in (133 cm) (Top of steering wheel)
Overall Height (With Canopy)	77.0 in (196 cm)
Wheel Base	78.5 in (199i cm)
Front Wheel Track	38.0 in (96 cm)
Rear Wheel Track	38.5 in (97 cm)
Gnd Clearance @ Differential	6.0 in (15 cm)
Cargo Box Width (inside)	44.0 in (112 cm)
Cargo Box Length (inside)	36.0 in (91 cm)
Cargo Box Depth (inside)	10.5 in (27 cm)
Cargo Box Capacity	9.6 cu ft (0.27 m3)
Cargo Box Material	Roto-molded polyethylene
Vehicle Power	
Power Source	4 cycle, 29.2 ci (480 cc)
Valve Train	V Twin Cylinder OHV
Horsepower (kW)	16.0 hp (11.9 kW) rated
Electrical System	Starter/Generator, solid-state regulator
Battery (Qty, Type)	One 12 Volt maintenance free
Key or Pedal Start	Pedal Start
Air Cleaner	Dry cartridge w/permanent pre-filter/remote air
Lubrication	Pressurized oil system
Oil Filter	Spin-on oi filter
Cooling System	Air cooled
Max Volume	6.0 gallon (22.7 L) tank
Drive Train	Continuously variable transmission (CVT)
Differential	Helical gears with manual lock-up

Vehicle Power Cont.	
Gear Selection	Forward-Reverse
Rear Axle Ratio	13.32:1
Performance	
Seating Capacity	2 Persons
Dry Weight	1110 lb (505 kg)
Curb Weight	1150 lb (525 kg)
Bed Load Capacity	500 lb (226 kg)
Vehicle load capacity	800 lb (360 kg)
Outside Clearance Circle	23.5 ft (7.2 m)
Intersecting Aisle Clearance	N/A
Speed (Level Ground)	16 mph ± 0.5 mph (25.7 kph ± 0.8 kph)
Towing Capacity	500 lb (225 kg)
Steering & Suspension	
Steering	Self-compensating rack and pinion
Front Suspension	Leaf springs with hydraulic shock absorbers
Rear Suspension	Leaf springs with hydraulic shock absorbers
Service Brake	Rear wheel hydraulic self-adjusting drum
Parking Brake	Hand operated
Front Tires	Turf Saver 20 x 10 - 10 Uni-Directional
Rear Tires	Turf Saver 20 x 10 - 10 Uni-Directional
Body & Chassis	
Frame	Welded steel with DuraShield™ powder coat
Front Body & Finish	Injection Molded TPO
Rear Body & Finish	Steel. Base coat/clear coat
Standard Color	Hunter Green

Some items shown may be optional equipment

CUSHMAN

OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*

Item	Std	Opt	Fld
TIRES & WHEELS:			
Front & Rear			
Turf Saver 20 x 10 - 10	X		
Stryker 22 x 9 - 10 Uni-directional		X	
COLORS:			
Body Color - Hunter Green	X		
Body Color - Ivory		X	
Body Color - Yellow		X	
Body Color - Orange		X	
Body Color - Bright White		X	
Body Color - Flame Red		X	
Body Color - Black		X	
Body Color - Electric Blue		X	
Body Color - Platinum		X	
Body Color - Inferno Red		X	
Body Color - Metallic Charcoal		X	
Body Color - Patriot Blue		X	
Body Color - Steel Blue		X	
Custom Body Color		X	
Pin Stripes:			
Pewter		X	
Black		X	
Silver		X	
Seating:			
Seat Color - Gray	X		
Seat Color - Tan		X	
Seat Color - Black		X	
Seat Color - Brown		X	
Seat Color - White		X	
Custom Seat Color		X	
HAULING & TOWING:			
Gas Spring Assisted Poly Bed	X		
Poly Bed w/ Electric Lift		X	
Aluminum Bed w/ Manual Lift		X	
Aluminum Bed w/ Electric Lift		X	
2 in (5 cm) Receiver (Rear)	X		
2 in (5 cm) Front Winch Receiver		X	
1 7/8 in (48 mm) Ball (Rcvr Reqd)		X	
Angle (Rcvr Reqd)		X	
Clevis (Rcvr Reqd)		X	
Clevis, Drop (Rcvr Reqd)		X	
Angle, Drop (Rcvr Reqd)		X	
1 7/8 in (48 mm) Ball, Drop (Rcvr Reqd)		X	

Item	Std	Opt	Fld
ELECTRICAL:			
Headlights	X		
Horn	X		
Low Oil Indicator	X		
Fuel Guage	X		
LED Headlights		X	
Taillights w/Brakelights		X	
Turn Signals with 4-Way Flashers		X	
Hour Meter		X	
OTHER PERFORMANCE:			
Engine Skid Plate	X		
Hydraulic Drum Brakes	X		
Front Brushguard	X		
Ash Tray		X	
Comfort Grip Steering Wheel		X	
Glove Box Door (Locking) Driver Side		X	
Glove Box Door (Locking) Passenger Side		X	
Glove Box Door (Locking) Set		X	
Front Basket Kit			X
Gun Holder, Floor Mount			X
Clay's Car Field Kit			X
CE Kit			X
International Shipping Option		X	
TRANSAXLE:			
Locking Rear Differential	X		
High Altitude Jetting 5K-9K ft (1524-2744 m)		X	
High Altitude Jetting 9K+ ft (2744 m)		X	
WEATHER PROTECTION:			
Sun Canopy (Top) Black			X
Weather Enclosure (3 Side, Top & Windshield Required)			X
Windshield Flat			X
Windshield Fold Down			X
Canopy Handle			X

Specifications are subject to change without notice
* Field installed accessories may require installation charges